


T8



- 265 mA
- 4' Lamp Applications
- OcTek™ Series Featured


UNIVERSAL® ELECTROMAGNETIC BALLASTS

FOR F32T8 and F32T8/U LAMPS

Fluorescent-Electromagnetic

Lamp		Line Volts	Catalog Number	Certification					Line Current (Amps)	Input Power (Watts)	Ballast Factor	Ballast Efficacy Factor	Crest Factor	THD %	Min. F/C Start Temp	Sound Rating	Wiring Diag.	Dim.
Qty.	Descr.			E	UL	SF	IEC	NOM										
F32T8 - High Power Factor OcTek®																		
2	Rapid	120	M232SR120C	•	•	•	•	.65	74	.95	1.28	< 1.7	< 20	50/10	A	1	D2	
2	Rapid	277	M232SR277C	•	•	•	•	.28	74	.95	1.28	< 1.7	< 20	50/10	A	1	D2	
F32T8/U - High Power Factor OcTek™																		
2	Rapid	120	M232SR120C	•	•	•	•	.65	74	.95	1.28	< 1.7	< 20	50/10	A	1	D2	
2	Rapid	277	M232SR277C	•	•	•	•	.28	74	.95	1.28	< 1.7	< 20	50/10	A	1	D2	

Overall Dimensions			Mounting Dimensions		
Draw #	L	W	H	M	X
D2	9 1/2	2 3/8	1 1/2	8 57/64	1 11/16



WIRING DIAGRAMS




DIAGRAM 1